64860581-000

LA NUOVA GAMMA DI GENERATORI A RAGGI-X

STRALE

CARATTERISTICHE PRINCIPALI	STRALE 100-500 BE	STRALE 300 BE	STRALE 500 BE 10	STRALE 100-1000 BE
Potenza	500W	300W	500W	1000W
Voltaggio tubo	20kV-100kV	20kV-80kV	20kV-100kV	20kV-100kV
Corrente tubo	0,5-6mA	0,5-6mA	0,5-10mA	0,5-15mA
Macchia focale (diverse macchie focali su richiesta)	EN 12543 0.6	EN 12543 0.6	EN 12543 1.2	EN 12543 1.5
	EN 60336 0.4	EN 60336 0.4	EN 60336 0.6	EN 60336 0.7
Uscita raggi (diverse uscite su richiesta)	80° x 30°	80° x 3°	80° x30°	80° x 30°
	80° x 3°		80° x 3°	80° x 3°
Filtrazione inerente	Finestra di BE 1 mm	Finestra di BE 1 mm	Finestra di BE 1 mm	Finestra di BE 1 mm
Duty cycle	100%	100%	100%	100%
Raffreddamento monoblocco	Acqua	Aria	Acqua	Acqua
Dimensioni e peso monoblocco	160x290x338mm 21kg	160x290x393mm 21kg	160x290x338mm 21kg	160x290x338mm 21kg
Alimentazione	90-260V	90-260V	90-260V	90-260V
Interfaccia	RS232/USB	RS232/USB	RS232/USB	RS232/USB
	Ethernet (su richiesta)	Ethernet (on request)	Ethernet (su richiesta)	Ethernet (su richiesta)

GILARDONI

IMAGING THE FUTURE SINCE 1947

GILARDONI S.p.A. a Socio Unico
Via Arturo Gilardoni, 1 - 23826 Mandello del Lario (LC) Italy +39 0341 705.111
cnd@gilardoni.it *gx@gilardoni.it* *www.gilardoni.it*

RESEARCH LABORATORIES RECOGNIZED "HIGHLY QUALIFIED"
WITH DECREE D.M. 9.10.1985 - L. 46/82 ART.4 - COMPANY CERTIFIED ISO 9001 ISO 13485

THE NEW RANGE OF X-RAY GENERATORS

STRALE

MAIN FEATURES	STRALE 100-500 BE	STRALE 300 BE	STRALE 500 BE 10	STRALE 100-1000 BE
Power	500W	300W	500W	1000W
Tube voltage	20kV-100kV	20kV-80kV	20kV-100kV	20kV-100kV
Tube current	0,5-6mA	0,5-6mA	0,5-10mA	0,5-15mA
Focal spot (different focal spots on request)	EN 12543 0.6	EN 12543 0.6	EN 12543 1.2	EN 12543 1.5
	EN 60336 0.4	EN 60336 0.4	EN 60336 0.6	EN 60336 0.7
X-ray beam type (different beam on request)	80° x 30°	80° x 3°	80° x30°	80° x 30°
	80° x 3°		80° x 3°	80° x 3°
Total filtration	BE Window 1 mm	BE Window 1 mm	BE Window 1 mm	BE Window 1 mm
Duty cycle	100%	100%	100%	100%
Monoblock cooling	Water	Air	Water	Water
Monoblock dimensions and weight	160x290x338mm 21kg	160x290x393mm 22kg	160x290x338mm 21kg	160x290x338mm 21kg
Mains supply	90-260V	90-260V	90-260V	90-260V
Interface	RS232/USB	RS232/USB	RS232/USB	RS232/USB
	Ethernet (on request)	Ethernet (on request)	Ethernet (on request)	Ethernet (on request)

GILARDONI

IMAGING THE FUTURE SINCE 1947

GILARDONI S.p.A. a Socio Unico
Via Arturo Gilardoni, 1 - 23826 Mandello del Lario (LC) Italy +39 0341 705.111
cnd@gilardoni.it *gx@gilardoni.it* *www.gilardoni.it*

RESEARCH LABORATORIES RECOGNIZED "HIGHLY QUALIFIED"
WITH DECREE D.M. 9.10.1985 - L. 46/82 ART.4 - COMPANY CERTIFIED ISO 9001 ISO 13485